

V-TAC

Meaningful Innovation.

50kW

Three Phase On-Grid Solar Inverter

10 YEAR WARRANTY



Multi MPP trackers



160% DC Input
oversizing



Smart I-V curve
diagnosis supported



DC&AC type II SPD



Intelligent fault
detection



AFCI function
(Optional)



IP66
rating

V-TAC.EU

|

VTACEXPORTS.COM

TUV NORD

CE RoHS

LISTING DETAILS

Model No: **VT-6607150**
 SKU Code: **11521**
 EAN Code: **3800157693554**

MASTER BOX PACKAGING

Net Weight : **50kg**
 Product Size : **650 x 450 x 260 mm**

INPUT (DC)

Max. Input Power **80kW**
 Max. Input Voltage **1100V**
 Start Voltage **250V**
 Rated Input Voltage **600V**
 Full-load MPP Voltage Range **520V ~ 850V**
 MPPT Voltage Range **200V ~ 1000V**
 Number of MPP Trackers **4**
 Number of string per MPPT **3 / 2 / 3 / 2**
 Max. Current per MPPT **39A / 26A / 39A / 26A**
 Max. Short Circuit Current per MPPT **48A / 32A / 48A / 32A**

GENERAL DATA

Operating Temperature Range **-30° C ~ +60° C**
 Cooling Method **Smart Cooling**
 Protection Degree **IP66**
 Max. Operating Altitude **4000m**
 Relative Humidity **0 ~ 100%**
 Topology **Transformerless**
 Night Power Consumption **<1W**
 Warranty **10 years**

COMMUNICATION

Display **LED / LCD / WiFi+App (Optional)**
 Communication **Standard : RS485 / USB
 Optional: WiFi / GPRS / Ethernet**

OUTPUT (AC)

Max. Output Current **79.7A**
 Rated Output Power **50kW**
 Max. Output Power **55kVA**
 Rated Grid Frequency **50Hz / 60Hz**
 Rated Grid Voltage **230Vac / 400Vac**
 Power Factor **>0.99 (0.8 leading~0.8 lagging)**
 THDi **<3% (Rated Power)**

STANDARD COMPLIANCE

Grid Connection Standards **IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE-AR-N 4110:2018, VDE-AR-N 4105:2018, VDE-AR-N 4120:2018, EN 50549, AS/NZS 4777.2:2020, CEI 0-21, VDE 0126-1-1/A1 VFR 2014, UTE C15-712-1:2013, DEWA DRRG, NRS 097-2-1, MEA/PEA, C10/11, G98/G99**

Safety / EMC **IEC 62109-1:2010, IEC 62109-2:2011, EN 61000-6-2:2005, EN 61000-6-3:2007/A1:2011**

EFFICIENCY

Max. Efficiency **98.70%**
 European Efficiency **98.40%**
 MPPT Efficiency **99.90%**

PROTECTION

DC reverse polarity protection **Yes**
 Anti-islanding protection **Yes**
 AC short circuit protection **Yes**
 Residual current monitoring unit **Yes**
 Insulation resistance monitoring **Yes**
 Ground fault monitoring **Yes**
 Grid monitoring **Yes**
 PV string monitoring **Yes**
 Surge protection **Type II**
 AFCI protection **Optional**



Efficient Higher Revenue

- 4 MPP Trackers, high single circuit tracking accuracy, fast dynamic response and higher power generation
- 160% DC Input Oversizing
- Maximum efficiency of 98.6%. Wide MPPT voltage range: 200V-1000V
- Compatible with high power modules



Intelligent Simple O&M

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- Intelligent Fault Detection: ac-side voltage and current waveforms real-time recorded, fast fault location
- Support RS485/USB (WiFi/GPRS/Ethernet optional): remote monitoring and operation via PC or mobile phones



Reliable Worry Free

- IP66 Protection degree: support outdoor installation
- DC & AC Type II SPD: prevent lightning damage
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

